



Escorts Kubota Limited (Construction Equipment)
Plot No. 219, Sector- 58, Ballabhgarh- 121 004, Faridabad, Haryana (INDIA)

Tel.: 0129-2306574/2306598/2306571

Fax: 0129-2306572 Website: www.escortsgroup.com

Fax: U129-2306572 Website: www.escortsgro

mail: ekl_g.ece.marketing@escortskubota.com

Toll Free No.: 1800-180-4488



Authorised Dealer

SILIG 30 CID'S NOTAIN

HD 85 PLUS TAKE THE ROAD AHEAD





Operating Weight 9 t



Fuel Efficient



Compaction Force
High



Gradeability
High



Low

. The information contained in this leaflet is intended to be of a popular actual within 4 EV.

SPECIFICATIONS

ENGINE ESCORTS E4.346CRS4 Make 4 Cylinder, Water Cooled. Type **CEV STAGE-IV Emission Norms** 75 HP @ 2000 RPM Rated Power

STEERING

Steering Angle ± 30° ± 10° Oscillation Angle 6 475 mm / 4 750 mm Turning Radius-outer/inner

WEIGHT Unit Operating Weight 9 120 kg 4 470 kg Weight on Front Drum Weight on Rear Drum 4 650 kg Static Linear Load Front/ Rear 26.6 / 27.7 kg cm Centrifugal Force per Drum, Low 6 020 kg Centrifugal Force per Drum, High 6 626 kg Total Applied Load Both Drums, Low 21 161 kg 22 372 kg Total Applied Load Both Drums, High

SPEED

0-8.5 km/h Working Travelling 0-13.8 km/h

GRADEABILITY

Gradeability Without Vibration 36% Gradeability With Vibration 30%

VIBRATION SYSTEM

33/50 Hz Frequency High Amplitude 1.0 mm Low Amplitude 0.4 mm

CAPACITY

Water Tank 800 I. Fuel Tank 160 I. Hydraulic Oil Tank 80 I.

ELECTRICAL SYSTEM

Battery 12V, 150AH

BRAKES

Service Brake Hydrostatic Parking Brake, Emergency Stop Spring Loaded Brake, Hydraulically released

on both drums

Foldable canopy frame to decrease height during transportation

Sprinkler Nozzles visible from operator seat

Water Pump, 2 nos. for uninterrupted operation

High kerb clearance for effective compaction

Swivel Operator seat including steering wheel, FNR lever and instrument panel for drum edge visibility

High Static Linear Load

Low Turning Radius

DIMENSIONS

Loading Height

Drum Diameter

Shell Thickness

Kerb Clearance

Ground Clearance

SALIENT FEATURES

· Sliding Operator Seat

· Double Water Pump

Tiltable Steering

· Collapsable Roof

· Fuel Level Gauge

SAFETY DEVICES · Neutral Start Switch

· Air Filter Clog Indicator

· Starter Safety Relay

· Vibration Delay Relay · Battery Cut off Switch

KEY FEATURES

Hydraulic Filter Clog Indicator

· Auto-Vibration & Sprinkler Cutoff

· Over & Long Cranking Protection

· Visual Warning Against Parking Brakes on

· Audio Visual Warning For High Coolant temperature & Low Lube Oil Pressure

· Water Level Gauge

Drum Width

Wheel Base

Height (With Canopy)

Length

Width

Unit

4 175 mm

1 780 mm

3 110 mm

2 680 mm

1 680 mm

1 200 mm

2 900 mm

290 mm


730 mm


17 mm

Compact Design









FEATURES



ENGINE

- 75 HP 4 Cylinder CEV STAGE-IV Emission Norms water cooled engine
- Best-in-class fuel economy
- High on performance
- Low maintenance cost



GRADEABILITY AND COMPACTION SYSTEM

- High Gradeability making it versatile for all applications
- Optimised setting Amplitude 1.0/0.4 mm with frequency 33/50 Hz
- Delay relay to avoid the sudden impact while switching from one frequency to another
- High Kerb clearance for better road edge compaction



INSTRUMENT PANEL

- Dust and Weather proof instrument panel
- IP 67 Compliant instrument panel and rocker switch for high reliability



OPERATOR PLATFORM

- Ergonomically designed space for operator comfort
- Foldable 2 post Canopy legs for ease of transportation
- Rotating platform with tiltable steering
- · Resilient rubber mounts, low vibration transfer to operator



OPTIMUM VISIBILITY

- 360° visibility
- Clear drum edge visibility from operator seat
- Compact design



SPRINKLING

- Sprinkling nozzles visible from operator seat • Sprinkling nozzles with three stage
- filtration to avoid clogging Tongue-type nozzles to avoid
- rusting
- Wide flat fan with a sharp delimited spray pattern for long last uses

HD 85 PLUS



HD 85 PLUS TAKE THE ROAD AHEAD

